





Enhanced Visibility and Protection

Sensata INSIGHTS' 4-Channel HD Vehicle Recorder, the CP4S, is a cloud-connected mini DVR. Designed to record high-resolution telematics data, the CP4S provides powerful insights into driving dynamics like harsh braking, cornering and accelerating. Increase driver blind-spot visibility with the support of up to 4 cameras and an optional monitor to capture video in and around vehicles. Cameras record the 10 seconds before and after an event and the event itself, and the CP4S automatically uploads event data to the cloud. Packed with sensors and high-speed connectivity, the CP4S provides real-time decision-making capabilities for operators and managers to coach drivers, capture incidents and reduce costs.

Highlights



Video collects contextual evidence to protect you and your drivers



Reduce vehicle blindspot footprints



Provide in-cab visibility to external views



Adaptable to almost any use case

Features

- 4G/LTE data transmission for real-time notification of events
- · Supports up to 4 cameras
- · HD video across all 4 channels
- Compatible with an in-cab LCD monitor
- Supports up to 256GB of storage
- · Compact, temper-resistant and secure design
- Built-in temperature logic for improved performance in high-temperature environments
- SD error/corruption detection with remote support and management

CP4S Technical Specifications

| Mechanical | |
|-------------------------|--|
| Size | 28 mm H x 120 mm W x 90 mm D / 1.1" H x 4.7" W x 3.5" D |
| Weight | 166 g |
| Electrical | |
| Power Input | 12/24V DC nominal |
| Power Consumption | Max. 36 W |
| Delayed Power Shutdown | Yes |
| Supercapacitor | Enables Recording of Last File & Safe Shutdown |
| Video Resolution | Supports HD (1080p) on Channel 1, HD (720p) on Channels 2~4 |
| Recording Speed | 4 Channels HD at 15 FPS |
| Recording Mode | Continuous, Event and Dual Mode |
| Storage | Supports SD Cards up to 256GB |
| AV In / Out | 1 x Audio In (internal/external microphone) / 1 x Video Out; 1 x Audio Out |
| Alarm In / Out | 4 x Alarm In / 1 x Alarm Out |
| LED | Green LED (network), Blue LED (recording), Red LED (error) |
| Environmental | |
| Operational Temperature | -10°C~+55°C |
| Communications | |
| Cellular | CP4S-NA [CAT4]: B2/B4/B5/B12/B13/B14/B66/B71 3G Bands: B2/B4/B5 |
| | CP4S-EU [CAT4]: B1/B3/B7/B8/B20/B28A/B38/B40/B41 3G Bands: B1/B8 |
| Positioning | |
| GNSS | External GPS/GLONASS |
| G-Sensor | Internal 3-Axis G-Sensor |
| Gyro | 3 Axis (X,Y,Z), Output Rate: 100 Hz |
| Compliance | |

FCC, AT&T, Verizon, CE, E-Mark, PTCRB, RoHS

2-Years Standard





sensata-cp4s-spec-sheet-americas_0123

Certification/Regulatory

Warranty